

## MINI MICRO BLOWN FIBRE 1.4 OPTIC CABLE

### APPLICATION

- ◆ Micro Duct
- ◆ FTTx and Access

MINI MICRO CABLES

### CONSTRUCTION

GRP/FRP	Glass reinforced plastic central strength, PE over sheathed in certain cases
LOOSE TUBE	PBT (Polybutylene Terephthalate) filled with thixotropic gel
FIBRES	12 colour coated fibres per tube
WATER BLOCKING	Core wrapping and overall
RIPCORD	Water blocked
SHEATHING	High Density Polyethylene (Black is the standard colour)

### MECHANICAL PROPERTIES


FIBRE COUNT	NUMBER OF ELEMENTS	CABLE DIAMETER NOMINAL (mm)	CABLE WEIGHT (kg/km)	MAXIMUM INSTALLATION LOAD (N)	BENDING RADIUS		SUITABLE MICRO DUCT SIZE
					LONG TERM	SHORT TERM	
Up to 72	6	5.4	28	400	20 x OD	12 x OD	10/8
96	8	6.3	38	600	20 x OD	12 x OD	10/8
144	12	8.0	60	600	20 x OD	12 x OD	12/10

### FIBRE AND BUFFER COLOURS AS TIA/EIA

1	Blue	2	Orange	3	Green	4	Brown	5	Grey	6	White
7	Red	8	Black	9	Yellow	10	Violet	11	Pink	12	Turquoise

### ORDERING INFORMATION

FIBRE COUNT	CABLE TYPE	FIBRE TYPE ITU-T	DRUM QUANTITY (m)
24	Micro Blown Cable (BLC 1.4)	G.657.A1 ULTRA 200	4000



## MINI MICRO BLOWN FIBRE 1.4 OPTIC CABLE

Page 2 of 2

MINI MICRO CABLES

OPTICAL PROPERTIES		
CHARACTERISTICS	ITU-T.657A1 ULTRA 200	
Modefield Diameter (µm)	1310nm	9.2 ± 0.4
	1550nm	10.4 ± 0.5
Cabled Attenuation (dB/km)	1310nm	± 0.34
	1550nm	± 0.20
Polarization Mode Dispersion (ps/√km)	Link (PMDQ)	≤ 0.04
	Individual (PMDmax)	≤ 0.1
Chromatic Dispersion (ps/nm.km)	1285-1330nm	3
	1550nm	≤ 18
	1625nm	≤ 22
Macro-Bend Loss	1550nm	Ø10mm, 1turn, ≤ 0.5dB
		Ø15mm, 10turns, ≤ 0.05dB
		Ø25mm, 100turns, ≤ 0.01dB
	1625nm	Ø10mm, 1turn, ≤ 1.5dB
		Ø15mm, 10turns, ≤ 0.3dB
		Ø25mm, 100turns, ≤ 0.01dB
Cladding Diameter (µm)		125 ± 0.7
Coating Diameter (µm)		200 ± 1
Cladding Non Circulatory (%)		≤ 1
Core-Clad Concentricity (µm)		≤ 0.6
Cable Cut-Off Wavelength (nm)		≤ 1260
Local Variations : Cabled (dB)		≤ 0.1@1550nm