

CBS Blowing Machine Comparison



	AccelAir 2	GentL Air	Whisper	AirStream	Hurricane	JetStream	Tornado
Cable Diameter:	0.8-3mm	1-3mm	2-8.5mm	2.5-11mm	2.5-16mm	4-20mm	① 6-32mm
Tube Size (OD):	3-10mm	4-8mm	5-18mm	5-18mm	5-25mm	12-50mm	12-63mm
Cable Speed (Adjustable):	0-50m/min	0-90m/min	0-90m/min	0-80m/min	0-85m/min	0-85m/min	0-90m/min
Max Air Pressure/Volume:	12bar/ .24m ³ min	15bar/ 1m ³ min	15bar/ 1m ³ min	15bar/ 1m ³ min	15bar/ 2m ³ min	② 15bar/ 12m ³ min	② 12bar/ 4-12m ³ min
Drive:	Drive Wheels	Drive Roller	Drive Roller	Drive Belts	Drive Belts	Drive Belts	Drive Belts
Cable Safety:	Buckle Protection*	Torque Limiting Clutch	Torque Control via Drill	Electronic Torque Control	Electronic Torque Control	Hydraulic Pressure Sensing	Hydraulic Pressure Sensing
Power:	110/220 VAC	Vari Speed Drill	Vari Speed Drill	110/220 VAC	110/220 VAC	Hydraulic**	Hydraulic**
Length:	120mm	246mm	246mm	460mm	550mm	620mm	1070mm
Width:	184mm	206mm	206mm	300mm	310mm	484mm	690mm
Height:	166mm	216mm	216mm	270mm	350mm	233mm	1230mm
Weight:	3kg	5.45kg	5.4kg	14kg	24kg	31kg	103kg

① Micro Duct (10 & 12mm OD) blowing available with add-on kit. ② Airflow is duct size dependent

*Buckle Protection only up to 1.6mm **Petrol hydraulic power pack supplied

CBS Products (KT), Ltd. Pillings Road, Oakham, Rutland, LE15 6QF, United Kingdom

Tel: +44 (0) 1572 723665 • E-mail: sales@cbsproducts.com • Website: www.cbsproducts.com